

GPSmile 62 Car Navigator (BASIC)



- OS : Microsoft Windows CE 5.0 Core Version
- CPU : Samsung S3C2443, 400 MHz
- Bluetooth 2.0, H/F 1.5
- 5.0" WQVGA (16:9)TFT LCD
- Removable Li-Ion battery. (1050 mAh)
- Multi-Language support
- UltraSlim design 14.5±0.5 mm

Specifications

- | | |
|---|---|
| <ul style="list-style-type: none">● CPU : Samsung S3C2443, 400 MHz● Display :<ul style="list-style-type: none">◇ 5.0" WQVGA(16:9) TFT LCD with touch screen , Brightness Typ. 300nits◇ 480x272 pixels● Touch screen : Resistive type touch screen● RAM: 64MB SDRAM● Flash Memory:<ul style="list-style-type: none">◇ 64MB NAND Flash (SLC)● GPS Receiver : *<ul style="list-style-type: none">◇ Internal Patch Antenna.◇ MTK 3318 chip◇ Tracking sensitivity -159dbM◇ Tracking: L1, C/A code◇ Channels: 32 parallel channels◇ Reacquisition: 0.1 sec.◇ Hot Start 1 sec. (Average.)◇ Warm Start: 33 sec. (Average.)◇ Cold Start: 36 sec. (Average.)◇ Position Accuracy: 3.0 m CEP without SA◇ Velocity: 0.1 m/sec.● Audio :<ul style="list-style-type: none">◇ Software volume control◇ Build in Speaker● USB : Support Mini USB connector (Compatible with USB specification V2.0) | <ul style="list-style-type: none">● Expansion : Support 4GB memory Card (SDHC)● Dimension :<ul style="list-style-type: none">Typ.134.5mm x 89mm x 14.5 mm (+/-0.5mm)● Weight :<ul style="list-style-type: none">Typ. 189 g (+/- 5g)● Temperature :<ul style="list-style-type: none">◇ Operation : -10°C ~ 60°C◇ Storage : -20°C ~ 60°C◇ Over heat battery protection: 45°C● Humidity :<ul style="list-style-type: none">◇ Operation : 0% ~ 85%◇ Storage : 0% ~ 85%● Certification & Regulation : CE/FCC/NCC● TMC Traffic Receiver (Optional)● Software :<ul style="list-style-type: none">◇ Photo View◇ GPS Map (Papago! X2 /iGo)● Multi-Language :<ul style="list-style-type: none">◇ USA English/English/French/German/Spanish/Italian/ Dutch/Portuguese◇ Traditional Chinese (CHT)/ Simplified Chinese (CHS)/ English |
|---|---|

* Cit.MTK's original chipset spec